



Medium

DOLCE81 S3

Safety shoe with zone traction and tripguard

Safety Jogger's DOLCE81 combines safety and comfort with SR slip resistance, water and oil resistance, heel energy absorption, and SJ Flex puncture resistance. Features like body posture pain relief and static spark protection make it versatile for various industries.

Upper	Nappa Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/Rubber
Toecap	Steel
Category	S3 / SRC
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.665 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK



SJ Flex
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.

Shoes For Crews
Shoes For Crews safety and occupational footwear provides enhanced traction, slip resistance when walking on different slippery surfaces and much more.

SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Oil & fuel resistant
The outsole is resistant against oil and fuel.

Water resistant Upper (WRU)
Prevents penetration of water if not permanently exposed to high levels.

Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:

Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Logistics, Oil & Gas, Industry

Environments:

Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nappa Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	4.5	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	48	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	69.4	≥ 2
	Lining: water vapor coefficient	mg/cm ²	555.4	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	130	≤ 150
	Outsole slip resistance SRA: heel	friction	0.39	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.37	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.29	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.34	≥ 0.18
	Antistatic value	MegaOhm	35.9	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	25	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	15.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.