

X1100N S3

Product Reference X1100N
 ENISO20345:2011 S3 SRC
 Sizes 5-5-13
 Weight (s. 8) 1.41 lb.

Model description: Leather shoe, water repellent, black, Cambrella lining, antistatic, puncture resistant SJ Flex sole, shock proof, slip resistant, composite toe cap, S3 PU/PU sole.

Application areas: Construction, Manufacturing.

Precaution and maintenance of the shoe: To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



1. Compression Resistance For Whole Footwear. ASTM F 2412-11, C/75.

	ASTM F2413 Requirement	Pass/Fail
Interior Height Clearance Left: 0.877 in	> 0.5 in	Pass
Right: 0.913 in	> 0.5 in	Pass

2. Puncture Resistance For Puncture Resistant Devices. ASTM F 2412-11, 11.

	ASTM F2413 Requirement	Pass/Fail
The test pin did not penetrate beyond the face of the material nearest the foot before 1200N.	Min. 1200N	Pass

3. Flex Resistance For Puncture Resistant Devices. ASTM F 24-11, 11.7.

	ASTM F2413 Requirement	Pass/Fail
Left: No signs of de-lamination of layers or cracking after 1.5 million flexes.	*	Pass
Right: No signs of de- lamination of layers or cracking after 1.5 million flexes	*	Pass

4. Impact Resistance For Whole Footwear. ASTM F 2412-11, I/75.

	ASTM F2413 Requirement	Pass/Fail
Interior Height Clearance Left: 0.657 in	> 0.5 in	Pass
Right: 0.700 in	> 0.5 in	Pass

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.